

Product Overview
CLASS Primer 190 is a ready-to-use copolymer primer agent based on an acrylic polymer dispersion, featuring high alkali resistance and excellent adhesion. It is designed to enhance adhesion strength prior to the application of topcoat plasters.

Application Domains
It serves as a primer for both interior and exterior facades prior to the application of decorative plaster in thermal insulation systems.

Technical Specifications

Intensity	1,50 ±0,03 kg/lit
Colour	White
Chemical Composition	Acrylic Copolymer-Based
Substantial Material	%10
Application Ground Temperature	+5 °C, +25 °C

The information presented in this technical data sheet is derived from experimental results. The responsibility for the proper application of our original product rests with the user. Our company is solely accountable for the product's quality. This data sheet supersedes the information provided in the previous version. Our company reserves the right to amend any information contained within this data sheet.

- Advantages**
- Prepared for use.
 - The application process is straightforward and efficient.
 - It is a water-based and odorless substance.
 - It is suitable for safe use in both indoor and outdoor environments.
 - It possesses significant adhesive strength.
 - It possesses excellent coverage capabilities. It solidifies the application surface.
 - It is applied prior to the application of cement and gypsum-based coatings to mitigate rapid water loss from the mortar.

Surface Preparation
The surfaces designated for coating must be entirely clean and dry, devoid of residues such as oil, dirt, dust, and rust. Comprehensive cleaning is crucial to guarantee optimal adhesion.

Mixture
The surface must be solid, devoid of loose and weak components, free from frost, and clean, without cement slurry, stagnant water, oil, grease, paraffin, coatings, or other foreign substances and contaminants. Mix in a clean container or its original packaging, free from any materials that may hinder adhesion, for a minimum of 3 minutes using a low-speed mixer.

Application Details
Apply the product to the surface using a brush, roller, or spray. Following application, safeguard against unfavorable weather conditions, including direct sunlight, strong winds, high temperatures (exceeding +35°C), rain, and frost. Before the product completely cures and hardens, cleanse your hands with water and detergent. The product may induce skin irritation. It is advisable to wear work clothing, protective gloves, a mask, and goggles. Additionally, a protective cream can be applied to the hands prior to commencing work. In the event of contact with the eyes, rinse immediately with warm water and seek medical attention.



Consumption

150-200 g/m² per coat, subject to variation based on surface absorbency.



PACKAGING

20 KG Plastic Bucket



Shelf life

In its unopened packaging, it can be stored for 12 months in a cool, dry location, shielded from sunlight, at temperatures ranging from +10°C to +25°C.



Attention

Avoid applications when the ambient temperature is below +5°C or above +30°C. Do not apply in direct sunlight, rain, or wind. Refrain from applying on surfaces that have been exposed to sunlight for extended periods, are frozen, or are at risk of freezing within 24 hours.

R10: Keep away from children.

R20/22: Harmful if inhaled or ingested.

R52/53: Toxic to aquatic life; may result in long-term detrimental effects in the aquatic ecosystem.

R65: Harmful. May result in lung damage if ingested.

S7: Store in a securely sealed container.

S24/25: Avoid contact with eyes and skin. S28: In the event of skin contact, rinse immediately with ample water.

S29: Do not release into the sewage system.

S46: If ingested, seek medical attention promptly and present the container or label.

LEGAL NOTICE

The information provided herein regarding BENZKİM CLASS products, particularly the recommendations concerning their application and end use, is presented in good faith based on BENZKİM CLASS's current knowledge and experience under standard conditions, provided that these products are stored and applied correctly in accordance with BENZKİM CLASS's guidelines. The variability of products, application surfaces, and application areas in practice is significant. Therefore, when utilizing BENZKİM CLASS products, it is imperative to apply the appropriate product under the correct conditions and in the designated location, while strictly adhering to the information and instructions provided by BENZKİM CLASS regarding commercial suitability and/or suitability for a specific purpose. Failure to do so may result in BENZKİM CLASS being absolved of any responsibility for potential damages. The product user is responsible for testing the product's suitability for the intended application and purpose. BENZKİM CLASS reserves the right to modify the properties of its products. The rights of third parties must be duly respected. All orders are accepted in accordance with our current terms and conditions pertaining to sales and shipping. Users are encouraged to consult the latest version of the local Product Information Sheet for the relevant product, which can be obtained by contacting BENZKİM CLASS.